

RICOH fi-7900 Datasheet

☑ Scanner



Advanced productivity for high-volume scanning

The fi-7900 scans A4 landscape documents at high speeds of 140 ppm/280 ipm (200/300 dpi). It is capable of scanning up to A3 sized portrait documents and can load up to 500 sheets at a time.

Accurate feeding to maximize productivity

Our production scanners are designed to build productive workflows. In addition to our reliable feeding, the fi-7900 comes with a variety of functionalities that make feeding performance even better. Finish scanning faster without the need to make any rescans, using the all-new Automatic Separation Control function. This new function automatically calibrates torque on the brake rollers and guarantees that documents go through one at a time. The fi-7900 now also comes with the fi Series signature Skew Reducer function providing independent separator rollers to ensure skewed documents do not affect documents to follow.

Organized paper output for clean and fast workflows

Not only do we ensure that paper is fed through smoothly but also that output is made in neat stacks. The improved Stacking Control function and Elevator Stacker allow operators to quickly gather documents after scanning so that operators can quickly move on to the next batch, and scan multiple batches in shorter times.

Stress-free usability with an operator-friendly design

The fi-7900 is designed to make the operator experience easy. Operators can scan directly from the scanner with the job-registration function, and complete various operations on the easily-accessible operator panel and LCD status display. Ease of use also applies to routine maintenance of the scanner. The fi-7900's LED lights make cleaning dust, debris, and ink residue build-up from the glass simply easy and stress-free.

Advanced software for maximized efficiency

Empower operator workflows and feed information efficiently with our latest PaperStream IP scanner driver and integrated software. With a few simple setting configurations, Automatic Profile Selection allows documents to undergo image processing appropriate to each document format. Operators no longer need to sort documents manually since the driver works with PaperStream Capture to link document formats to specific saving destinations. Image processing functionalities are also enhanced with Advanced Cleanup Technology providing strong character recognition and image cleanup functionalities for better OCR accuracy. All these functionalities work together to offer a wider variety of batch scanning features and assist operator workflows.

Technical Information

Scanner Type	ADF (Automatic Document Feeder) / Manual Feed,		
Scanner type			
Conning Coord*1	Duplex		
Scanning Speed ^{*1}	Circular 140 (200/200 -li)		
(A4 Landscape)	Simplex: 140 ppm (200/300 dpi)		
(Colour*2/Grayscale*2/	Duplex : 280 ipm (200/300 dpi)		
Monochrome*3)			
Scanning Speed ^{*1}			
(A4 Portrait)	Simplex: 105 ppm (200/300 dpi)		
(Colour ^{*2} /Grayscale ^{*2} /	Duplex : 210 ipm (200/300 dpi)		
Monochrome*3)			
Image Sensor Type	Colour CCD x 2 (front x 1, back x 1)		
Light Source	White LED Array x 4 (front x 2, back x 2)		
Optical Resolution	600 dpi		
Output Resolution*4	E0 to 600 dpi (adjustable by 1 dpi increments)		
(Colour / Grayscale /	50 to 600 dpi (adjustable by 1 dpi increments),		
Monochrome)	1,200 dpi (driver)*5		
Output Format	Colour: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit		
Background Colours	White / Black (selectable)		
Document Size			
Maximum	304.8 x 431.8 mm (12 x 17 in.)		
Minimum	52 x 74 mm (2 x 3 in.)		
Long Page Scanning*6	5,588 mm (220 in.)		
Paper Weight (Thickness)			
A4 to A5 Size	20 to 209 g/m ² (5.4 to 56 lb)		
Less than A5 Size /	41 to 209 g/m ² (11 to 56 lb)		
Over A4 Size			
ADF Capacity*7	500 sheets (A4 80 g/m ² or Letter 20 lb)		
Expected Daily			
Volume ^{*8}	120,000 sheets		
Multifeed Detection	Overlap detection (Ultrasonic sensor),		
	Length detection		
Paper Protection	Lag detection		
Interface	USB 2.0 / USB 1.1		
Power Requirements	AC 100 to 240 V ±10 %		
Power Consumption			
Operating Mode	200 W or less		
Sleep Mode	3.2 W or less		
Auto Standby (Off)	Less than 0.3 W		
Mode			
Operating Environment	I		
Temperature	5 to 35 °C (41 to 95 °F)		
Relative Humidity	20 to 80% (non-condensing)		

Environmental	ENERGY STAR [®] , RoHS		
Compliance			
Dimensions*9			
(Width x Depth x	460 x 430 x 310 mm (18.1 x 16.9 x 12.2 in.)		
Height)			
Weight	32 kg (70 lb)		
Supported	Windows [®] 11 ^{*10} , Windows [®] 10 ^{*10} ,		
Operating System	Windows Server [®] 2022, Windows Server [®] 2019,		
	Windows Server [®] 2016, Windows Server [®] 2012 R2,		
	Windows Server [®] 2012		
Software / Drivers	PaperStream IP Driver (TWAIN/TWAIN x64/ISIS),		
	WIA Driver ^{*11} , PaperStream Capture,		
	PaperStream Clic	kScan ^{*12} , Software Operation Panel,	
	Error Recovery Guide, Scanner Central Admin Server		
Image Processing	Multi image outp	out, Automatic colour detection, Blank	
Functions	page detection, Static threshold, Dynamic threshold		
	(iDTC), Advanced DTC, SDTC, Error diffusion, Dither,		
	De-Screen, Emphasis, Dropout colour (None/Red/		
	Green/Blue/White/Saturation/Custom), sRGB output,		
	Hole punch remo	oval, Cropping, Index tab cropping,	
	Split image, De-Skew, Edge correction, Vertical streaks reduction, Character extraction, Background pattern removal, Automatic profile selection		
Included Items	AC cable, USB cable, Setup DVD-ROM		
Options			
Post Imprinter		For standard stations and show the	
(FI-680PRF)	PA03575-D201	Front-side printing on document	
Post Imprinter			
(FI-680PRB)	PA03575-D203	Back-side printing on document	
PaperStream Capture		PaperStream Capture Pro	
Pro MV Production	PSCP-MV-0001	optional license	
Consumables			
Pick Roller	PA03575-K011	Every 600,000 sheets or one year	
Separator Roller	PA03800-K012	Every 600,000 sheets or one year	
Brake Roller	PA03575-K013	Every 600,000 sheets or one year	
Print Cartridge	CA00050-0262	4,000,000 printed characters or	
		6 months after opening the bag	

*1 Scanning speeds may vary due to the system environment. For details, please visit our website at: https://www.pfu.ricoh.com/global/scanners/fi/. *2 Indicated speeds are from using JPEG compression. *3 Indicated speeds are from using TIFF CCITT Group 4 compression. *4 When scanning in high resolutions (500 dpi or above), scanning may be rejected depending on scanning mode, document size, memory size, and application program. Selectable maximum resolution may vary depending on the length of the scanned document. *5 Limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). *6 Documents between 431.8 mm (17 in.) and 863 mm (34 in.) in length are limited to 400 dpi. Documents between 863 mm and 3,175 m (1/25 in.) in length are limited to 300 dpi. *7 Maximum capacity depends on paper weight and may vary. *8 Numbers are calculated using scanning speeds and typical hours of scanner use, and are not meant to guarantee daily volume or unit durability. *9 With the ADF hopper closed. *10 fi Series scanners do not run with Windows® 11 and 10 ARM-based PCs. *11 Functions equivalent to those offered by PaperStream IP may not be available with the WIA Driver. *12 Refer to the fi Series Support Site for driver/software downloads and full lineup of all supported operating system versions.

Trademarks

ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings. ENERGY STAR®

PFU Limited has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

PFU Canada Inc.

https://www.pfu-ca.ricoh.com

Have a question? Email us at: sales@pfu-ca.ricoh.com

RICOH and RICOH logo are registered trademarks of Ricoh Co., Ltd. Other product names are the trademarks or registered trademarks of the respective companies.

Specifications are subject to change without notice. Visit the fi Series website for more information. https://www.pfu-ca.ricoh.com/scanners © 2024 PFU Canada Inc. All rights reserved.